

TYPE: CP092

### CONDIZIONATORE PORTATILE 9000 BTU

- Climatizzatore portatile 9000 BTU, Elettronico, semplice da collocare pronto all'uso: per Raffrescare, Deumidificare, Ventilare.
- Controllo elettronico e telecomando.
- Display visualizza ogni funzione e la temperatura ambiente.
- Funzioni: Freddo / Deumidificazione / Ventilazione.
- Modalità: Normal / Sleep.
- Ventilazione: Hi / Low.
- Timer 24h: temporizza Start e/o Stop.
- Termostato ambiente regolabile.
- Bocchetta di uscita aria con alette regolabili.
- Ingresso aria con filtri lavabili.
- Kit finestra: Tubo estensibile 15x145cm (Ø \* L max-), Barre (3) adattate a finestra/tapparella (L= 124-172cm).
- Base con ruote, e valvola drenaggio acqua.
- Capacità nominale (max): Freddo 9000BTU (2,64kW)
- Consumo nominale (max): Freddo 1010W
- Indice efficienza energetica: Freddo EER 2,6
- Classe efficienza energetica: Freddo A
- Portata aria: 350m<sup>3</sup>/h - Deumidificatore: 24 l/giorno
- Rumore: 55 dB (A) - Gas: R290 (210g)
- Temperatura impiego 7-35°C
- Idoneo per 14-20m<sup>2</sup>
- 220-240V~ 50Hz 1023W



### PORTABLE AIR CONDITIONER 9000 BTU

- 9000 BTU Portable air conditioner, electronic, simple to place, ready to use: for Cooling, Dehumidifying, Ventilating.
- Electronic control and Remote control.
- Display shows each function and the room temperature.
- Functions: Cold / Dehumidification / Ventilation.
- Mode: Normal / Sleep.
- Ventilation: Hi / Low.
- 24h timer: times Start and/or Stop.
- Adjustable room thermostat (cooling function).
- Air conditioning outlet with adjustable louvers.
- Air inlet with washable filters.
- Window kit: 15x145cm (Ø \* L max) Extendable pipe, Bars (3) adaptable to window/shutter (L= 124-172cm).
- Base with wheels and water drainage valve.
- Rated capacity (max): Cold 9000BTU (2.64kW)
- Nominal consumption (max): Cold 1010W
- Energy efficiency index: Cold EER 2.6
- Energy efficiency class: Cold A
- Air flow: 350m<sup>3</sup>/h - Dehumidifier: 24 l/day
- Noise: 55 dB (A) - Gas: R290 (210g)
- Operating temperature 7-35°C
- Suitable for 14-20m<sup>2</sup>
- 220-240V~ 50Hz 1023W



EAN: 8016117024558

PEZZI PER MASTER / PCS FOR PACKING: 1

PEZZI PER BANCALE / PCS FOR PALLET: 12